

## **Displaying Modeling Results:** How to display and reclassify Maxent results in ArcMap

Though maxent results can be seen in a picture format, you can have much more control over the visualization using ArcMap.

1. To access the model output file, open ArcMap, and Arc Toolbox. In the toolbox, go to **Conversion Tools** > **To Raster** > **ASCII to Raster**.



2. Select the maxent output ASCII file (be sure the files of type is set to .asc) for the input file, and choose a directory and name for your output (ersi grid file). Choose "float" so that the decimals are maintained and click OK.

≁ ASCII to Raster	
Input ASCII raster file	<u>^</u>
C:\WorkSpace\Intro_SDM\CA_tutorial\output\Vireo_bellii_pusillus.asc	
Output raster	
C:\WorkSpace\Intro_SDM\CA_tutorial\output\Vireo_belli	- 🖻
Output data type (optional)	
FLOAT	-
	~
Cancel Environments	how Help >>



3. Once completed, you will see a greyscale image of the results.

4. There are many tools available in the layer properties which can be accessed by double clicking the layer name in the table of contents, and choose the **Symbology** tab.

Layer Properties			? 🔀
General Source Extent	Display Symbology Fields Joins & Relates		
Show: Unique Values	Draw raster stretching values along a color ramp	Import.	
Classified Stretched			^
	Color Value Label		
	0.988923 High : 0.988923		
	0.000005 Low : 5.40733e-006	_	Ξ
	Color Ramp:	•	
	Display Background Value: 0 as	-	
	Use hillshade effect Z; 1 Display NoData as	-	
	Stretch Type: None Istograms.		
	☐ <u>I</u> nvert		
	ОК	Cancel	Apply

5. For example, choose "Minimum-Maximum" as the Stretch Type, and a color ramp of your choice. You can click apply to see the results, or check the Edit High/Low Values box to change these values.

Layer Properties	S 🛛 🕄
General Source Extent	Disnlau Symbology Fields Joins & Belates
Chown	Display Company of Total Company
<u>D</u> now:	Draw raster stretching values along a color ramp Import
Classified Stretched	
	Color Value Label
	0.988923 High: 0.988923
	Edit High/Low Values 🔽
	0.000005 Low : 0.000005
	Color Kamp:
	Display Background Value:
	Use hillshade effect Z: 1 Display NoData as
	Stretch
	Type: Minimum-Maximum 🗹 Histograms
QUntitled - ArcMap - ArcInf	
Eile Edit View Bookmarks Insert	: Selection Tools Window Help
	X ⋈ ⋈ ♣ 🛛 🗸 🔊 🕲 🖕 № 3 🕲 🖉 🔍 🔍 🔍 🐨 🗸 🖏
● ● ** *2 @ <b>●</b> ●	
🗆 🛃 Layers	ArcToolbox
Vireo_belli Value	So Analyst Tools  So Analysis Tools
High : 0.988923	😧 🏧 Cartography Tools
Low : 5.40733e-006	E S From Raster
	From WFS
	Coverage Do Coverage Do Coverage
	To Geodatabase
	E S To KML
	ASCII to Raster
	CEM to Raster Feature to Raster
	Ploat to Raster
	Point to Raster
	Polyline to Raster
	Raster To Other Form
	R S IO shapene
	Data Intercopreduity Tools
	Geocoding Tools
	Geostatistical Analyst Tools
	B Mobile Tools
	W Wiltidimension Tools W So Network Analyst Tools
	B Samples
	Comparison of the second
	Spatial Analyst Tools
Display Source Selection	Favorites Index Search Results 0 0 2 4 4
Drawing 🕶 📐 💿 🚳 🗖 🖛	A ▼ 🖾 🖉 Anal 🔍 10 ▼ B I U A ▼ 🅭 ▼ 🥒 ▼ 📩 ▼ Editor ▼ ト 🖉 ▼ Task: Create New Feature

6. Next, we can reclassify the image in order to delimit a binary result. Make sure that the Spatial Analyst Extension is checked on: **Tools** > **Extensions**, and access the Spatial Analyst toolbar through **View** > **Toolbars** > **Spatial Analyst**.

Spatial Analyst		×
Spatial <u>A</u> nalyst 🔻	Layer: Vireo_belli	💽 🚀 📐

7. Go to Reclassify in the Spatial Analyst drop down menu. And click on the "Classify" button to access the Classification menu.

Reclassify			? 🔀				
Input raster:	Vireo_bell	i	<b>•</b>				
Reclass field:			•				
Set values to reclassif	у ———						
Old values 0.000005 - 0.003868 0.003868 - 0.007731 0.007731 - 0.011594	N 0 1 2	ew values	Classify				
0.015457 - 0.01932	3 4		Add Entry				
<	ш		Delete Entries				
Load	Save	Classification					? 🔀
	es he MeDe	Classification				-Classification Statistics -	
Output raster:	<tempor< td=""><td>Method: Manual</td><td> Sa</td><td>mpling</td><td></td><td>Count: Minimum: Maximum: Sum: Mean: Standard Deviation:</td><td>24175 0.000005 0.988923 965.128883 0.039923 0.096978</td></tempor<>	Method: Manual	Sa	mpling		Count: Minimum: Maximum: Sum: Mean: Standard Deviation:	24175 0.000005 0.988923 965.128883 0.039923 0.096978
		C <u>o</u> lumns: 100 📫	Show Std. De	v. 🗖 Show	Mea <u>n</u>		
		15000- 8				0.988923	Break Values <u>%</u> 0.105 0.988923
		10000					
		5000-					
		0	0.247235	0.494464	0.741694	0.988923	ОК
		🗖 Snap breaks to data 👳	alues			10899 Elements in Class	Cancel

8. In the classification menu, choose "2" for the number of classes, and enter the desired threshold in the **Break Values**. You can consult the maxent html output for a table of suggested thresholds. Click OK.

9. Back in the Classify menu, change the new value for the lower range "NoData" and change the range for the positive values as "1". Choose an output directory and file name, and click **OK**.

Reclassify		? 🔀			
Input raster:	Vireo_belli	- 🖻			
Reclass field:		•			
Set values to reclase	sify				
Old values	New values	Classify			
0.000005 - 0.105	0	Unique			
0.105 - 0.988923	1				
		Add Entry			
		Delete Entries			
Load Save Precision					
Change missing va	lues to NoData				
Output raster: C:\WorkSpace\Intro_SDM\CA_tutorial\CA_extent					
	ОК	Cancel			

9. You should see the resulting file in the map, where all of the positive areas equal "1" and the negative areas equal "0".



## **RS/GIS Quick Start Guides**

These materials are freely available for use and modification through a Creative Commons Attribution-Share Alike 3.0 License. License details: <u>http://creativecommons.org/licenses/by-sa/3.0/us/</u> Version: Original document was created by GIF (2008)

